

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

1 Identification

- **Product name**
- **Trade name:** Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM
- **Item number:** 98-8810
- **CAS Number:**
27804-64-4
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Strem Chemicals, Inc.
7 Mulliken Way
NEWBURYPORT, MA 01950
USA
info@strem.com
- **Information department:** Technical Department
- **Emergency telephone number:**
EMERGENCY: CHEMTREC: + 1 (800) 424-9300
During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.
Water-react. 2 H261 In contact with water releases flammable gas.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.
Acute Tox. 3 H311 Toxic in contact with skin.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements**
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS06



GHS07

(Contd. on page 2)

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

· **Hazard statements**

H226 Flammable liquid and vapor.

H261 In contact with water releases flammable gas.

H301+H311 Toxic if swallowed or in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· **Precautionary statements**

P223 Do not allow contact with water.

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 3

The substance demonstrates unusual reactivity with water.

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

27804-64-4 Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

US

(Contd. on page 3)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

US
(Contd. on page 4)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 3)

7 Handling and storage

- **Handling:** Handle under inert gas.
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** Store contents under inert gas.
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:** Not required.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Colorless
· Odor:	Odorless
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	<-10 °C (<14 °F)
· Boiling point/Boiling range:	70 °C (158 °F)

· **Flash point:** > 30 °C (> 86 °F)

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Not determined.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 0.804 g/cm³ (6.709 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· Organic solvents:	0.0 %
· VOC content:	0.0 g/l / 0.00 lb/gl

(Contd. on page 6)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Substance is not listed.

· **NTP (National Toxicology Program)**

Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016




Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN3399
· UN proper shipping name · DOT, IATA · IMDG	Organometallic substance, liquid, water-reactive, flammable ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
· Transport hazard class(es) · DOT	
	
· Class · Label	4.3 Substances which, in contact with water, emit flammable gases 4.3, 3
· IMDG	
	
· Class · Label	4.3 Substances which, in contact with water, emit flammable gases 4.3/3
· IATA	
	
· Class · Label	4.3 Substances which, in contact with water, emit flammable gases 4.3 (3)
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number: · Stowage Category · Stowage Code	Not applicable. F-G,S-N D SW2 Clear of living quarters.

(Contd. on page 8)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 7)

· Handling Code	<i>H1 Keep as dry as reasonably practicable</i>
· Segregation Code	<i>SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. SG35 Stow "separated from" acids.</i>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· DOT	
· Quantity limitations	<i>On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L</i>
· IMDG	
· Limited quantities (LQ)	<i>500 ml</i>
· Excepted quantities (EQ)	<i>Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</i>
· UN "Model Regulation":	<i>UN 3399 ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE, 4.3 (3), II</i>

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (extremely hazardous substances):
<i>Substance is not listed.</i>
· Section 313 (Specific toxic chemical listings):
<i>Substance is not listed.</i>
· TSCA (Toxic Substances Control Act):
<i>Substance is not listed.</i>
· Proposition 65
· Chemicals known to cause cancer:
<i>Substance is not listed.</i>
· Chemicals known to cause reproductive toxicity for females:
<i>Substance is not listed.</i>
· Chemicals known to cause reproductive toxicity for males:
<i>Substance is not listed.</i>
· Chemicals known to cause developmental toxicity:
<i>Substance is not listed.</i>
· Carcinogenic categories
· EPA (Environmental Protection Agency)
<i>Substance is not listed.</i>
· TLV (Threshold Limit Value established by ACGIH)
<i>Substance is not listed.</i>

(Contd. on page 9)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS06 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

· **Hazard statements**

H226 *Flammable liquid and vapor.*

H261 *In contact with water releases flammable gas.*

H301+H311 *Toxic if swallowed or in contact with skin.*

H332 *Harmful if inhaled.*

H315 *Causes skin irritation.*

H319 *Causes serious eye irritation.*

H335 *May cause respiratory irritation.*

· **Precautionary statements**

P223 *Do not allow contact with water.*

P231+P232 *Handle under inert gas. Protect from moisture.*

P301+P310 *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*

P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Water hazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Technical Department.*

· **Contact:** *Technical Director*

· **Date of preparation / last revision** *08/01/2016 / -*

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 10)

Safety Data Sheet
according to OSHA HCS

Printing date 08/01/2016

Reviewed on 08/01/2016

Trade name: Bis(diethylamino)silane, 99% (99.999%-Si) BDEAS PURATREM

(Contd. of page 9)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

US