MSDS Number: B0231 * * * * * Effective Date: 03/02/11 * * * * * Supersedes: 04/17/08



morennegercy questions should be directed to castomer service, 1-055-XHARTON (055-202-0007) of assis

BTS-220

1. Product Identification

Synonyms: Propylene Glycol Monomethyl Ether Acetate; 1-Methoxy-2-Propanol Acetate CAS No.: 108-65-6 Molecular Weight: 132.16 Chemical Formula: C6H12O3 Product Codes: 6304, 6314, 6333, 6343

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Propylene glycol monomethyl ether acetate	108-65-6	100%	Yes

3. Hazards Identification

Emergency Overview

WARNING! COMBUSTIBLE LIQUID AND VAPOR. MAY FORM EXPLOSIVE PEROXIDES. MAY CAUSE IRRITATION TO EYES AND RESPIRATORY TRACT.

SAF-T-DATA(**tm**) Ratings (Provided here for your convenience)

Health Rating: 1 - Slight Flammability Rating: 2 - Moderate Reactivity Rating: 2 - Moderate Contact Rating: 1 - Slight Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER Storage Color Code: Red (Flammable)

Potential Health Effects

Inhalation:
Inhalation of high concentrations may cause irritation to the respiratory tract.
Ingestion:
Not expected to be a health hazard via ingestion.
Skin Contact:
May be absorbed through the skin.
Eye Contact:
High vapor concentrations may cause eye irritation.
Chronic Exposure:
No information found.
Aggravation of Pre-existing Conditions:
Persons with pre-existing eye disorders or impaired respiratory function may be more susceptible to the effects of this material.

4. First Aid Measures

Inhalation:

Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion:

If large amounts were swallowed, give water to drink and get medical advice.

Skin Contact:

Wash exposed area with soap and water. Get medical advice if irritation develops.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

5. Fire Fighting Measures

Fire:

Flash point: 42C (108F) CC Autoignition temperature: 354C (669F) Flammable limits in air % by volume: lel: 1.5; uel: 7.0

Combustible Liquid and Vapor! Contact with strong oxidizers may cause fire.

Explosion:

Sealed containers may rupture when heated. Above the flash point, explosive vapor-air mixtures may be formed. Vapors can flow along surfaces to distant ignition source and flash back. May form unstable peroxides which may explode spontaneously or when heated.

Fire Extinguishing Media:

Water spray, dry chemical, alcohol foam, or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or

spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. After opening, purge container with nitrogen before re-closing. Periodically test for peroxide formation on long-term storage. Do not distill to near dryness. If peroxide formation is suspected, do not open or move container. Addition of water or appropriate reducing materials will lessen peroxide formation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do Not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

For Propylene Glycol Monomethyl Ether Acetate:

- AIHA Workplace Environmental Exposure Level (WEEL) -

100 ppm (TWA).

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, wear a supplied air, full-facepiece respirator, airlined hood, or full-facepiece self-contained breathing apparatus.

Skin Protection:

Wear protective gloves and clean body-covering clothing.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Clear, colorless liquid. Odor: Sweet ether-like odor. Solubility: Appreciable in water. Specific Gravity: 0.969 @ 20C (68F) pH: No information found. % Volatiles by volume @ 21C (70F): No information found. Boiling Point:

```
150C (302F)
Melting Point:
No information found.
Vapor Density (Air=1):
4.6
Vapor Pressure (mm Hg):
3.7 @ 20C (68F)
Evaporation Rate (BuAc=1):
0.39
```

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Unstable at elevated temperatures. May form explosive peroxides.

Hazardous Decomposition Products:
Carbon dioxide and carbon monoxide may form when heated to decomposition.
Hazardous Polymerization:
Will not occur.
Incompatibilities:
Oxidizers can cause vigorous reaction.
Conditions to Avoid:
Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

For Propylene Glycol Monomethyl Ether Acetate: LD50 oral rat 8532 mg/kg; LD50 skin rabbit > 5 gm/kg.

\Cancer Lists\					
	NTP Carcinogen				
Ingredient	Known	Anticipated	IARC Category		
Propylene glycol monomethyl ether	No	No	None		

12. Ecological Information

Environmental Fate:

No adverse ecological effects are expected.

Environmental Toxicity:

This material is not expected to be toxic to aquatic life. The LC50/96-hour values for fish are over 100 mg/l. The EC50/48-hour values for daphnia are over 100 mg/l.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE) Hazard Class: 3 UN/NA: UN1993 Packing Group: III Information reported for product/size: 425LB

International (Water, I.M.O.)

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE) Hazard Class: 3 UN/NA: UN1993 Packing Group: III Information reported for product/size: 425LB

International (Air, I.C.A.O.)

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE) Hazard Class: 3 UN/NA: UN1993 Packing Group: III Information reported for product/size: 425LB

15. Regulatory Information

\Chemical Inventory Status - Part Ingredient	1\	TSCA	EC	Japan	Australia	
Propylene glycol monomethyl ether acetate (108-65-6)		Yes	Yes	Yes	Yes	
\Chemical Inventory Status - Part	2\		Ca	anada		
Ingredient		Korea	DSL	NDSL	Phil.	
Propylene glycol monomethyl ether acetate (108-65-6)		Yes	Yes	No	Yes	
\Federal, State & International Regulations - Part 1\						
Ingredient	- SARA RQ	TPQ	Lis	st Cher	nical Catg.	
Propylene glycol monomethyl ether acetate (108-65-6)	No	No	No		No	
\Federal, State & International Regulations - Part 2\						
Ingredient	CERCL	A 2	261.33	1: 3 8	(d)	

Propylene glycol monomethyl ether No No No acetate (108-65-6)

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes Chronic: No Fire: Yes Pressure: No Reactivity: No (Pure / Liquid)

Australian Hazchem Code: None allocated. Poison Schedule: None allocated. WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 1 Flammability: 2 Reactivity: 0

Label Hazard Warning:

WARNING! COMBUSTIBLE LIQUID AND VAPOR. MAY FORM EXPLOSIVE PEROXIDES. MAY CAUSE IRRITATION TO EYES AND RESPIRATORY TRACT.

Label Precautions:

Avoid breathing vapor or mist.

Avoid contact with eyes, skin and clothing.

Keep away from heat, sparks and flame.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

If inhaled, remove to fresh air. Get medical attention for any breathing difficulty. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. If large amounts were swallowed, give water to drink and get medical advice.

Product Use:

Laboratory Reagent.

Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE. continued THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.

Prepared by: Environmental Health & Safety