

Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

42.07 **Document Group:** 08-1308-9 **Version Number:** 01/29/14 Issue Date: **Supercedes Date:** 12/11/13

SECTION 1: Identification

1.1. Product identifier

3MTM NovecTM Engineered Fluid 7200

Product Identification Numbers

98-0211-9362-2, 98-0211-9363-0, 98-0211-9367-1, 98-0211-9368-9, 98-0212-3404-6, 98-0212-4838-4, 98-0211-9368-9, 98-0212-3404-6, 98-0210-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-020-6, 98-

1.2. Recommended use and restrictions on use

Recommended use

For Industrial Use Only. Not Intended for Use as a Medical Device Or Drug., Solvent for Cleaning and Coating; Heat Transfer Fluid

Restrictions on use

NovecTM Engineered Fluids are used in a wide variety of applications, including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Electronics Markets Materials Division ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Page 1 of 10

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

Notes to Physician:

Not applicable

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--------------------------------|-------------|---------|
| Ethyl nonafluorobutyl ether | 163702-05-4 | 20 - 80 |
| Ethyl nonafluoroisobutyl ether | 163702-06-5 | 20 - 80 |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide **Condition**

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid skin contact with hot material. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Store work clothes separately from other clothing, food and tobacco products. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------------|------------|--------------|---------------------------|----------------------------|
| Ethyl nonafluorobutyl ether | 163702-05- | Manufacturer | TWA(as total isomers):200 | |

| | 4 | determined | ppm | |
|--------------------------------|------------|--------------|---------------------------|--|
| Ethyl nonafluoroisobutyl ether | 163702-06- | Manufacturer | TWA(as total isomers):200 | |
| | 5 | determined | ppm | |

Amer Conf of Gov. Indust. Hyg.: American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid: Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Apron - polymer laminate

Respiratory protection

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid **Specific Physical Form:** liquid

Odor, Color, Grade: Clear colorless liquid with faint odor

Odor threshold No Data Available Not Applicable pН

-138 °C **Melting point** 76°C **Boiling Point**

Flash Point No flash point

33 [Ref Std: BUOAC=1] **Evaporation rate**

Flammability (solid, gas) Not Applicable

Flammable Limits(LEL) 210 g/m3 [Details: ASTM E681-94 Method] Flammable Limits(UEL) 1070 g/m3 [*Details*: ASTM E681-94 Method]

Vapor Pressure 109 mmHg [@ 25 °C] **Vapor Density** 9.1 [*Ref Std:* AIR=1]

Density 1.43 g/ml

Specific Gravity 1.43 [*Ref Std:* WATER=1]

Solubility in Water

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water 4.2 [Details: at 30 °C]

Autoignition temperature 375 °C [Details: ASTM E659-78 Method]

Decomposition temperature Not Applicable 0.4 centistoke Viscosity Percent volatile 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents

10.6. Hazardous decomposition products

Condition Substance

Hydrogen Fluoride At Elevated Temperatures - extreme conditions of

Perfluoroisobutylene (PFIB) At Elevated Temperatures - extreme conditions of

heat

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

Page 5 of 10

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------------------|-------------|---------|--------------------|
| Ethyl nonafluoroisobutyl ether | Inhalation- | Rat | LC50 > 989 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| Ethyl nonafluoroisobutyl ether | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Ethyl nonafluorobutyl ether | Inhalation- | Rat | LC50 > 989 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| Ethyl nonafluorobutyl ether | Ingestion | Rat | LD50 > 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--------------------------------|---------|---------------------------|
| Ethyl nonafluoroisobutyl ether | Rabbit | No significant irritation |
| Ethyl nonafluorobutyl ether | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--------------------------------|---------|---------------------------|
| Ethyl nonafluoroisobutyl ether | Rabbit | No significant irritation |
| Ethyl nonafluorobutyl ether | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--------------------------------|---------|-----------------|
| Ethyl nonafluoroisobutyl ether | Guinea | Not sensitizing |
| | pig | |
| Ethyl nonafluorobutyl ether | Guinea | Not sensitizing |
| | pig | |

Respiratory Sensitization

| Name | Species | Value |
|--------------------------------|---------|---|
| Ethyl nonafluoroisobutyl ether | | Data not available or insufficient for classification |
| Ethyl nonafluorobutyl ether | | Data not available or insufficient for classification |

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------------------|----------|---------------|
| Ethyl nonafluoroisobutyl ether | In Vitro | Not mutagenic |
| Ethyl nonafluoroisobutyl ether | In vivo | Not mutagenic |
| Ethyl nonafluorobutyl ether | In Vitro | Not mutagenic |
| Ethyl nonafluorobutyl ether | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------------------|-------|---------|---|
| Ethyl nonafluoroisobutyl ether | | | Data not available or insufficient for classification |
| Ethyl nonafluorobutyl ether | | | Data not available or insufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------------------|------------|--|---------|-----------------------------|----------------------|
| Ethyl nonafluoroisobutyl ether | Ingestion | Not toxic to reproduction and/or development | Rat | NOAEL 1,000 mg/kg | 28 days |
| Ethyl nonafluoroisobutyl ether | Inhalation | Not toxic to reproduction and/or development | Rat | NOAEL 3,000 ppm | |
| Ethyl nonafluoroisobutyl ether | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluoroisobutyl ether | Inhalation | Not toxic to female reproduction | Rat | NOAEL 260.1 mg/l | during gestation |
| Ethyl nonafluoroisobutyl ether | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluoroisobutyl ether | Inhalation | Not toxic to male reproduction | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluoroisobutyl ether | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 260 mg/l | during gestation |
| Ethyl nonafluorobutyl ether | Ingestion | Not toxic to reproduction and/or development | Rat | NOAEL 1,000 mg/kg | 28 days |
| Ethyl nonafluorobutyl ether | Inhalation | Not toxic to reproduction and/or development | Rat | NOAEL 3,000 ppm | |
| Ethyl nonafluorobutyl ether | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluorobutyl ether | Inhalation | Not toxic to female reproduction | Rat | NOAEL 260.1 mg/l | during gestation |
| Ethyl nonafluorobutyl ether | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluorobutyl ether | Inhalation | Not toxic to male reproduction | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluorobutyl ether | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 260 mg/l | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Specific Turget Organ | premie ruiget organ romeity single exposure | | | | | | | |
|--------------------------|---|------------------------|-----------------------------------|---------|-------------|------------|--|--|
| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure | | |
| | | | | | | Duration | | |
| Ethyl nonafluoroisobutyl | Inhalation | cardiac | Some positive data exist, but the | Dog | NOAEL 204 | 17 minutes | | |
| ether | | sensitization | data are not sufficient for | | mg/l | | | |
| | | | classification | | | | | |
| Ethyl nonafluoroisobutyl | Inhalation | respiratory irritation | All data are negative | Rat | NOAEL 989 | 4 hours | | |

| ether | | | | | mg/l | |
|-----------------------------|------------|------------------------|-----------------------------------|-----|-----------|------------|
| Ethyl nonafluorobutyl ether | Inhalation | cardiac | Some positive data exist, but the | Dog | NOAEL 204 | 17 minutes |
| | | sensitization | data are not sufficient for | | mg/l | |
| | | | classification | | _ | |
| Ethyl nonafluorobutyl ether | Inhalation | respiratory irritation | All data are negative | Rat | NOAEL 989 | 4 hours |
| | | | - | | mg/l | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------------|------------|--|--|---------|-----------------------------|----------------------|
| Ethyl nonafluoroisobutyl ether | Inhalation | liver kidney and/or bladder respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluoroisobutyl ether | Inhalation | heart endocrine system bone marrow hematopoietic system immune system nervous system | All data are negative | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluoroisobutyl ether | Ingestion | blood liver kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluoroisobutyl ether | Ingestion | heart endocrine system bone marrow hematopoietic system immune system nervous system respiratory system | All data are negative | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluorobutyl ether | Inhalation | liver kidney and/or bladder respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluorobutyl ether | Inhalation | heart endocrine system bone marrow hematopoietic system immune system nervous system | All data are negative | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Ethyl nonafluorobutyl ether | Ingestion | blood liver kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Ethyl nonafluorobutyl ether | Ingestion | heart endocrine system bone marrow hematopoietic system immune system nervous system respiratory system | All data are negative | Rat | NOAEL 1,000 mg/kg/day | 28 days |

Aspiration Hazard

| nopirution nuzuru | | | | | | |
|--------------------------------|--------------------------|--|--|--|--|--|
| Name | Value | | | | | |
| Ethyl nonafluoroisobutyl ether | Not an aspiration hazard | | | | | |
| Ethyl nonafluorobutyl ether | Not an aspiration hazard | | | | | |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Page 8 of 10

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 08-1308-9 **Version Number:** 42.07 **Issue Date:** 01/29/14 **Supercedes Date:** 12/11/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com