

Product: Silane

P-4649-F

Date: September 2004

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Silane (MSDS No. P-4649-F)		Trade Name: Silane	
Chemical Name: Silicon tetrahydride		Synonyms: Monosilane, silicon hydride, silicon tetrahydride, silicane	
Formula: SiH ₄		Chemical Family: Inorganic hydride	
Telephone:	Emergencies: 1-800-645-4633*	Company Name:	Praxair, Inc.
	CHEMTREC: 1-800-424-9300*		39 Old Ridgebury Road
	Routine: 1-800-PRAXAIR		Danbury, CT 06810-5113

* Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

2. Composition/Information on Ingredients

See section 16 for important information about mixtures.

INGREDIENT	CAS NUMBER	CONCENTRATION	OSHA PEL	ACGIH TLV-TWA (2004)
Silane	7803-62-5	>99%*	None currently established.	5 ppm

*The symbol > means "greater than."

3. Hazards Identification

EMERGENCY OVERVIEW

DANGER! Pyrophoric, flammable, high-pressure gas.
Can ignite on contact with air.
May form explosive mixtures with air.
Does not need a source of ignition.
Respiratory irritant.
May cause respiratory system damage.
Self-contained breathing apparatus and protective clothing
may be required by rescue workers.
Odor: Choking

THRESHOLD LIMIT VALUE: TLV-TWA, 5 ppm (ACGIH, 2004). TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

Product: Silane

P-4649-F

Date: September 2004

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:**INHALATION**—May cause headache, nausea, and irritation of the respiratory tract.**SKIN CONTACT**—No information available.**SWALLOWING**—An unlikely route of exposure. This product is a gas at normal temperature and pressure.**EYE CONTACT**—No information available.**EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:** No information available.**OTHER EFFECTS OF OVEREXPOSURE:** None known.**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:** The toxicology and the physical and chemical properties of this product suggest that overexposure is unlikely to aggravate existing medical conditions.**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:** None known.**CARCINOGENICITY:** Silane is not listed by NTP, OSHA, or IARC.

4. First Aid Measures

INHALATION: Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.**SKIN CONTACT:** Wash with soap and water. If irritation persists, seek medical attention.**SWALLOWING:** This product is a gas at normal temperature and pressure.**EYE CONTACT:** Flush eyes with water. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. If irritation persists, seek medical attention.**NOTES TO PHYSICIAN:** *There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.*

5. Fire Fighting Measures

FLASH POINT (test method):	Not applicable
-----------------------------------	----------------

AUTOIGNITION TEMPERATURE:	Not available
----------------------------------	---------------

FLAMMABLE LIMITS IN AIR , % by volume:	LOWER: Approximately 1% UPPER: 96%
---	--

EXTINGUISHING MEDIA: Gas may ignite spontaneously in air. (Fire cannot be extinguished.)**SPECIAL FIRE FIGHTING PROCEDURES: DANGER! Pyrophoric, flammable high-pressure gas.** Evacuate all personnel from danger area. Do not use halon fire extinguisher. Do not approach area without self-contained breathing apparatus and protective clothing. Immediately spray cylinders with water from maximum distance until cool. Reverse flow into cylinder may cause rupture. (See section 16.) Stop flow of gas if without risk, while continuing cooling water spray. If flow of gas cannot be shut off, allow fire to burn out. Reduce combustion products with water spray or fog. Remove all cylinders from area if without risk. If fire is extinguished while gas is present, explosive reignition may occur. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

Product: Silane

P-4649-F

Date: September 2004

UNUSUAL FIRE AND EXPLOSION HAZARDS: Gas may ignite spontaneously in air. At low ambient temperatures and high rates of flow, ignition may be delayed; and under sonic flow conditions, may not occur. Vapors may spread. Flammable vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. May form explosive mixtures with air. Heat of fire can build pressure in cylinder and cause it to rupture. No part of a cylinder should be subjected to a temperature higher than 125°F (52°C). Silane cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.)

HAZARDOUS COMBUSTION PRODUCTS: Hydrogen, silica dust, amorphous silicon dioxide. Powder produced by the decomposition of silane in the absence of air may be flammable. See section 10.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: DANGER! Pyrophoric, flammable high-pressure gas. May ignite spontaneously in air. Forms explosive mixtures with air. (See section 5.) Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus and protective clothing where needed. Reduce combustion products with fog or fine water spray. Reverse flow into cylinder may cause rupture. (See section 16.) Shut off flow if without risk. Ventilate area or move cylinder to a well-ventilated area. Prevent waste from contaminating surrounding environment.

EMERGENCY DISPOSAL: Silane, silane mixtures, and silane purge or vent gases can be readily treated to destroy the silane by several means:

- Burning the silane by slowly bleeding silane-containing gases into a continuously burning pilot light
- Venting the silane-containing gases slowly into the air through a water seal and allowing the silane to self-ignite and burn in an isolated area away from personnel
- Scrubbing the silane through a caustic bed or caustic solution (10% sodium hydroxide)
- Reacting the silane with aqueous mercuric chloride

WASTE DISPOSAL METHOD: Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE: Store and use with adequate ventilation. Separate cylinders containing this product from oxygen, chlorine, and other oxidizers by at least 20 ft (6.1 m) or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post “No Smoking or Open Flames” signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING: Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. All piped silane systems and associated equipment must be grounded. Electrical equipment must be non-sparking or explosion-proof. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object

(e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using silane, see section 16.

For further information on storage, handling, and use of this product, see NFPA 55, *Standard for the Storage, Use, and Handling of Compressed and Liquefied Gases in Portable Cylinders*, published by the National Fire Protection Association.

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST—Use an explosion-proof local exhaust system with sufficient airflow velocity to prevent oxygen deficiency and keep hazardous fumes and gases below applicable TLVs in the worker’s breathing zone.

MECHANICAL (general)—Not recommended as a primary ventilation system to control worker’s exposure.

SPECIAL—None

OTHER—None

RESPIRATORY PROTECTION: Use an air-supplied respirator or a full-face, positive-pressure, self-contained breathing apparatus. Respiratory protection must conform to OSHA 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.

SKIN PROTECTION: Wear work gloves when handling cylinders.

EYE PROTECTION: Wear safety glasses when handling cylinders. Select eye protection in accordance with OSHA 29 CFR 1910.133.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Fire-resistant clothing, ear protection, and face shields are recommended when connecting or disconnecting transfer lines. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

9. Physical and Chemical Properties

MOLECULAR WEIGHT:	32.117
SPECIFIC GRAVITY (Air = 1) at 70°F (21.1°C) and 1 atm:	1.109
GAS DENSITY at 68°F (20°C) and 1 atm:	0.0838 lb/ft ³ (1.342 kg/m ³)
SOLUBILITY IN WATER:	Negligible
PERCENT VOLATILES BY VOLUME:	100
BOILING POINT at 1 atm:	-169.87°F (-112.15°C)
MELTING POINT at 1 atm:	-301°F (-185°C)

APPEARANCE, ODOR, AND STATE: Colorless gas at normal temperature and pressure; choking odor.

Product: Silane

P-4649-F

Date: September 2004

10. Stability and Reactivity

STABILITY: Unstable Stable

NOTE: Silane is stable as shipped and when stored, handled, and used under the conditions specified in sections 7, 10, and 16 of this MSDS. Silane must not be exposed to air or moisture.

INCOMPATIBILITY (materials to avoid): Air, water, solutions of bases, oxidizing agents, chlorine, and halogens will react violently with halocarbons.

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen, silica dust, amorphous silicon dioxide. Powder produced by the decomposition of silane in the absence of air may be flammable. (Note: Minimum ignition energy may be less than 5 mJ. Kst may be greater than 400 bar meters-seconds⁻¹.)

HAZARDOUS POLYMERIZATION: May Occur Will Not Occur

CONDITIONS TO AVOID: Temperatures in excess of 752°F (400°C)

11. Toxicological Information

LC₅₀ = 19,000 ppm, 1hr, rat. See section 3.

12. Ecological Information

No adverse ecological effects expected. Silane does not contain any Class I or Class II ozone-depleting chemicals. Silane is not listed as a marine pollutant by DOT.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

DOT/IMO SHIPPING NAME: Silane

HAZARD CLASS: 2.1 **IDENTIFICATION NUMBER:** UN 2203 **PRODUCT RQ:** None

SHIPPING LABEL(s): FLAMMABLE GAS

PLACARD (when required): FLAMMABLE GAS

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

Product: Silane

P-4649-F

Date: September 2004

U.S. FEDERAL REGULATIONS:**EPA (ENVIRONMENTAL PROTECTION AGENCY)****CERCLA:** COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):**Reportable Quantity (RQ):** None**SARA:** SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:**SECTIONS 302/304:** Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):**TPQ:** None**EHS RQ:** None**SECTIONS 311/312:** Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:**IMMEDIATE:** Yes**PRESSURE:** Yes**DELAYED:** No**REACTIVITY:** Yes**FIRE:** Yes**SECTION 313:** Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Silane does not require reporting under Section 313.

40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION: Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Silane is listed as a regulated substance in quantities of 10,000 lb (4636 kg).

TSCA: TOXIC SUBSTANCES CONTROL ACT: Silane is listed on the TSCA inventory.**OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:****29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Silane is not listed in Appendix A as a highly hazardous chemical. However, any process that involves a flammable gas on site in one location in quantities of 10,000 lb (4536 kg) or greater is covered under this regulation unless the gas is used as a fuel.

STATE REGULATIONS:**CALIFORNIA:** Silane is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).**PENNSYLVANIA:** Silane is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

16. Other Information

Be sure to read and understand all labels and instructions supplied with all containers of this product.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE: *Pyrophoric, flammable high-pressure gas.* Use piping and equipment adequately designed to withstand pressures to be encountered. Use only in a closed system thoroughly purged with an inert gas prior to introduction of silane from cylinder. Use only spark-proof tools and explosion-proof equipment. Keep away from heat, sparks, and open flame. Close cylinder valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **Store and use with adequate ventilation.** Isolate from all other products. **Follow safe practices when returning cylinder to supplier.** Be sure valve is closed; then tightly install valve outlet cap or plug. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, state, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

NOTE: *Prior to using any plastics, confirm their compatibility with silane.*

Recommended Equipment: In semiconductor process gas and other suitable applications, Praxair recommends the use of engineering controls such as gas cabinet enclosures, automatic gas panels (used to purge systems on cylinder changeout), excess-flow valves throughout the gas distribution system, double containment for the distribution system, and continuous gas monitors.

MIXTURES: When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

HAZARD RATING SYSTEMS:

NFPA RATINGS:

HEALTH = 1
 FLAMMABILITY = 4
 INSTABILITY = 2
 SPECIAL = None

HMIS RATINGS:

HEALTH = 0
 FLAMMABILITY = 4
 PHYSICAL HAZARD = 3

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-350
PIN-INDEXED YOKE: CGA-None
ULTRA-HIGH-INTEGRITY CONNECTION: CGA-632

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

AV-1 *Safe Handling and Storage of Compressed Gases*
 P-1 *Safe Handling of Compressed Gases in Containers*
 V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
 — *Handbook of Compressed Gases, Fourth Edition*

Silane

Product: Silane

P-4649-F

Date: September 2004

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current Praxair MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from www.praxair.com. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

Praxair and the *Flowing Airstream* design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and other countries.



Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113