

GC THORSEN (GC ELECTRONICS) -- SILICONE RESIN LACQUER 22-245, 22-204 -- 8010-00F000564

=====
===== Product Identification =====

Product ID:SILICONE RESIN LACQUER 22-245, 22-204

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000564

MSDS Number: BBGXX

=== Responsible Party ===

Company Name:GC THORSEN (GC ELECTRONICS)

Address:1801 MORGAN ST

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Info Phone Num:815-968-9661

Emergency Phone Num:815-968-9661

CAGE:EO502

=== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

Company Name:GC THORSEN (GC ELECTRONICS)

Address:1801 MORGAN ST

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO502

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICONE-EPOXY RESIN SYSTEM

Fraction by Wt: 18%

Ingred Name:TOLUENE (IARC CARC- GROUP 3) *97-2*

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 52%

Other REC Limits:375 MG/CUM

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HYDROCARBON PROPELLANT

Fraction by Wt: 30%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DIZZINESS, NAUSEA.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:DIZZINESS, NAUSEA.

=====
First Aid Measures
=====

First Aid:INHALATION: GET FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:OC

Flash Point:30F

Extinguishing Media:CO2, FOAM

Fire Fighting Procedures:VENTILATE AREA WELL.

Unusual Fire/Explosion Hazard:DON'T USE/STORE NEAR FLAME/AT TEMPERATURE ABOVE 120F AS CAN MAY BURST.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA WELL. REMOVE ALL SOURCES OF IGNITION.

===== Handling and Storage =====

Handling and Storage Precautions:DONN'T USE/STORE NEAR HEAT/FLAME/AT TEMPERATURES ABOVE 120F AS CAN MAY BURST.

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230F

Spec Gravity:0.9

Evaporation Rate & Reference:(N-BUAC=1): 1.3

Solubility in Water:INSOLUBLE

Appearance and Odor:AROMATIC HYDROCARBON, CLEAR

Percent Volatiles by Volume:82

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.