



Ultradel R760

ULTRADEL®
Rinse Solu

MATERIAL SAFETY DATA SHEET

MSDS No. 10644
ENGLISH

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ULTRADEL® R760

MANUFACTURER/SUPPLIER:
Amoco Chemical Company
200 East Randolph Drive
Chicago, Illinois 60601 U.S.A.

EMERGENCY HEALTH INFORMATION:
1 (800) 447-8735
EMERGENCY SPILL INFORMATION:
1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT SAFETY INFORMATION:
(312) 856-3304

2.0 COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	Range % by Wt:
Isopropanol (isopropyl alcohol)	67-63-0	100

(See Section 8.0, "Exposure Controls/Personal Protection", for exposure guidelines)

3.0 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Warning! Flammable. Causes eye irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Inhalation causes headaches, dizziness, drowsiness, nausea, and respiratory irritation. If swallowed, causes headaches, dizziness, drowsiness and nausea, and may lead to unconsciousness.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: Causes eye irritation.

SKIN CONTACT: Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

INHALATION: Inhalation causes headaches, dizziness, drowsiness, nausea, and respiratory irritation.

INGESTION: If swallowed, causes headaches, dizziness, drowsiness and nausea, and may lead to unconsciousness.

HMIS CODE: (Health:2) (Flammability:3) (Reactivity:0)

NFPA CODE: (Health:2) (Flammability:3) (Reactivity:0)

4.0 FIRST AID MEASURES

- EYE:** Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.
- SKIN:** Wash exposed skin with soap and water. Remove contaminated clothing and thoroughly clean and dry before reuse. Get medical attention if irritation develops.
- INHALATION:** If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.
- INGESTION:** If swallowed, drink plenty of water, induce vomiting. Get medical attention.

5.0 FIRE FIGHTING MEASURES

- FLASHPOINT:** 53°F(11°C) ASTM D56
- UEL:** 12%
- LEL:** 2%
- AUTOIGNITION TEMPERATURE:** Not determined.
- FLAMMABILITY CLASSIFICATION:** Flammable Liquid.
- EXTINGUISHING MEDIA:** Agents approved for Class B hazards (e.g., dry chemical, carbon dioxide, foam, steam) or water fog.
- UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapor may explode if ignited in enclosed area. Product gives off vapors that are heavier than air which can travel considerable distances to a source of ignition and flashback.
- FIRE-FIGHTING EQUIPMENT:** Firefighters should wear full bunker gear, including a positive pressure self-contained breathing apparatus.
- PRECAUTIONS:** Keep away from sources of ignition (e.g., heat and open flames). Keep container closed. Use with adequate ventilation.
- HAZARDOUS COMBUSTION PRODUCTS:** Burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

6.0 ACCIDENTAL RELEASE MEASURES

- Remove or shut off all sources of ignition. Remove mechanically or contain on an absorbent material such as dry sand or earth.

7.0 HANDLING AND STORAGE

- HANDLING:** Keep away from ignition sources (e.g., heat, sparks, or open flames). Use with adequate ventilation.
- STORAGE:** Store away from heat, ignition sources, and open flame in accordance with applicable regulations. Store in flammable liquids storage area. Keep adequately ventilated. Keep container closed. Segregate from acids.

8.0 EXPOSURE CONTROLS / PERSONAL PROTECTION

- EYE:** Do not get in eyes. Wear chemical goggles.
- SKIN:** Avoid prolonged or repeated skin contact. Wear protective clothing and gloves if prolonged or repeated contact is likely.
- INHALATION:** Use with adequate ventilation. If ventilation is inadequate, use NIOSH/MSHA certified respirator that will protect against organic vapor and dust/mist.
- ENGINEERING CONTROLS:** Control airborne concentrations below the exposure guidelines.
- EXPOSURE GUIDELINES:**

<u>Component</u>	<u>CAS#</u>	<u>Exposure Limits</u>
Isopropanol (isopropyl alcohol)	67-63-0	OSHA PEL: 400 ppm (1989)(1971) OSHA STEL: 500 ppm (1989); Not established. (1971) ACGIH TLV-TWA: 400 ppm ACGIH TLV-STEL: 500 ppm

9.0 CHEMICAL AND PHYSICAL PROPERTIES

- APPEARANCE AND ODOR:** Liquid. Clear. Colorless. Alcohol odor.
- pH:** Not determined.
- VAPOR PRESSURE:** Not determined.
- VAPOR DENSITY:** Not determined.
- BOILING POINT:** 179°F(82°C) (ATSM D86)
- MELTING POINT:** Not determined.
- SOLUBILITY IN WATER:** Totally soluble.
- SPECIFIC GRAVITY (WATER = 1):** 0.789 at 60°F ASTM D4052
- VISCOSITY:** Less than 2 cP at 20°C

10.0 STABILITY AND REACTIVITY

- STABILITY:** Burning can be started easily.
- CONDITIONS TO AVOID:** Keep away from ignition sources (e.g. heat, sparks, and open flames).
- MATERIALS TO AVOID:** Incompatible with strong oxidizing agents, aluminum, strong acids, halogen, amines, and aldehydes.
- HAZARDOUS DECOMPOSITION:** None identified.
- HAZARDOUS POLYMERIZATION:** Will not occur.

11.0 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY DATA:

EYE IRRITATION: Testing not conducted. See Other Toxicity Data.

SKIN IRRITATION: Testing not conducted. See Other Toxicity Data.

DERMAL LD50: Testing not conducted. See Other Toxicity Data.

ORAL LD50: Testing not conducted. See Other Toxicity Data.

INHALATION LC50: Testing not conducted. See Other Toxicity Data.

OTHER TOXICITY DATA:

Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on information from similar products, the ingredients, technical literature, and/or professional experience.

Isopropanol: Overexposure to isopropanol vapor can cause a narcotic effect and irritation of the eyes and upper respiratory passages. A single lethal dose for a human is about 250 ml, although as little as 100 ml can be fatal. Rat oral LD50: 5045 mg/kg; rabbit dermal LD50: 12,800 mg/kg.

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

12.0 ECOLOGICAL INFORMATION

Ecological testing has not been conducted on this product.

13.0 DISPOSAL INFORMATION

Disposal must be in accordance with applicable federal, state, or local regulations. Determine waste classification at time of disposal. Conditions of use may render the spent product a hazardous waste. Enclosed-controlled incineration is recommended unless directed otherwise by applicable ordinances.

The container for this product can present explosion or fire hazards, even when emptied! To avoid risk of injury, do not cut, puncture, or weld on or near this container. Since the emptied containers retain product residue, follow label warnings even after container is emptied.

14.0 TRANSPORTATION INFORMATION**U.S. DEPT OF TRANSPORTATION**

Shipping Name	:	Isopropanol
Hazard Class	:	3
Identification Number	:	UN1219
Packing Group	:	II

INTERNATIONAL INFORMATION:**Sea (IMO/IMDG)**

Shipping Name	:	Isopropanol
Class	:	3.2
Packing Group	:	II
UN Number	:	UN1219

Air (ICAO/IATA)

Shipping Name	:	Isopropanol
Class	:	3
Packing Group	:	II

European Road/Rail (ADR/RID)

Shipping Name	:	Not determined.
---------------	---	-----------------

Canadian Transportation of Dangerous Goods

Shipping Name	:	Isopropanol
Hazard Class	:	3.2
UN Number	:	UN1219
Packing Group	:	II

15.0 REGULATORY INFORMATION

CERCLA SECTIONS 102A/103 HAZARDOUS SUBSTANCES (40 CFR PART 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR PART 355): This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA TITLE III SECTIONS 311/312 HAZARDOUS CATEGORIZATION (40 CFR PART 370): This product is defined as hazardous by OSHA under 29 CFR Part 1910.1200(d). Hazardous categories for this product are: Acute = yes; Chronic = no; Fire = yes; Pressure = no; Reactive = no.

SARA TITLE III SECTION 313 (40 CFR PART 372): This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

U.S. INVENTORY (TSCA): Listed on inventory.

This product contains isopropanol (CAS 67-83-0) which is currently undergoing review and testing under TSCA Section 4. Notification to the U.S. EPA Office of Toxic Substances is required prior to export of this material from the United States.

OSHA HAZARD COMMUNICATION STANDARD: Flammable liquid. Irritant. CNS Effects.

WHMIS CONTROLLED PRODUCT CLASSIFICATION: D2B, B2.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (MITI): Listed on inventory.

AUSTRALIA INVENTORY (AICS): Listed on inventory.

KOREA INVENTORY (ECL): Not determined.

CANADA INVENTORY (DSL): All of the components of this product are listed on the DSL.

PHILIPPINE INVENTORY (PICCS): Not determined.

16.0 OTHER INFORMATION

BY:



Donald M. Barker, Director
Product Stewardship & Toxicology

Issued: November 22, 1994
Supersedes: July 25, 1994

This material Safety Data Sheet conforms to the requirements of ANSI Z400.1.

This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in this data sheet which we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission or recommendation for the use of a product in a manner that might infringe existing patents. No warranty is made, either express or implied.